

Regavolt®**Enclosed Variable Transformers****Features**

- Enhanced Safety
- Thermal cut-out
- Portable
- Strong construction
- Bench or wall mounting
- Connections via IEC320
- Indication as standard
- Gold plated contact area
- No waveform distortion
- No harmonic generation
- High efficiency
- Continuously variable output 0 to 115%
- Manufactured in EEC
- CE Marked
- Safety to EN61010



CLAUDE LYONS
— IN CONTROL —

700 Series 230V nominal input voltage single phase

Model	No meters	710-EB
	Analogue Metering	710-EA
	Digital Metering	710-ED
Rated Current		10A
Load Rating		2.76 kVA
Output Voltage	<i>Over-voltage connection 115% of input</i>	
No-Load Loss		30W
Approx. weight		15kg
Number of turns on winding		258

Specification – 700 Series

Input supply voltage : 230V single phase

Input frequency : 47 to 65Hz

Input indication : Power ON lamp

Input connection : IEC320 socket

Output voltage : 0 to 115% of input

Output rating : see above tables

Output connection : IEC320 socket

Analogue display : $\pm 5\%$ fsd (Voltage calibrated 240V $\pm 2.5\%$)

Digital display : $\pm 1\%$ sinusoidal waveforms

Protection : Three pole thermal circuit breaker

Ambient : 0°C to +40°C

Humidity : 0 to 95% rh non-condensing

Dimensions (mm) : 300(h) x 212(w) x 200(d)

Standard accessories : 2 metre input mains lead and IEC320 output Socket.

Optional accessories : 2 metre output lead fitted with safety block 2 metre output lead fitted with 4 way sockets

E&OE eHoused Regavolt issue 2003/a

Due to continuous improvements Claude Lyons reserve the right to change specifications without notice

Claude Lyons Ltd. Brook Road, Waltham Cross, Hertfordshire. EN8 7LR. UK.

Tel : + 44 (0)1992 768888 Fax : + 44 (0) 1992 788000 Email: info@claudelyons.co.uk

www.claudelyons.co.uk